

**Certification  
Issued Under the Authority of the  
Federal Communications Commission  
By:**

**Compliance Certification Services  
561F Monterey Road  
Morgan Hill, CA 95037  
United States**

**Date of Grant: 02/24/2004  
Application Dated: 02/24/2004**

**Teletronics International Inc  
1803 Research Blvd  
Suite 404  
Rockville, MD 20850  
United States**

**Attention: Nusrat Jamal , Vice President**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER:** MFM-11-136  
**Name of Grantee:** Teletronics International Inc  
**Equipment Class:** Digital Transmission System  
**Notes:** 802.11b WLAN Card

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
CE	15C	2412.0 - 2462.0	0.233		

Output power listed is conducted. Limited Modular Approval - operation of this module in portable exposure conditions with respect to section 2.1093 of FCC rules is limited as follows: SAR compliance has been established in the laptop computer(s) configurations with PCMCIA slot configurations (e.g., side near the rear) as tested in this filing, and can be used in laptop computers with substantially similar physical dimensions, construction, and electrical and RF characteristics. A class II permissive change filing demonstrating SAR compliance in other host types, e.g. PDA, is required to allow operation in those host types. Compliance of this device in all final host configurations is the responsibility of the Grantee. End-users must be provided with specific information required to satisfy RF exposure compliance for all final host devices. The antenna(s) used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. Highest reported SAR value is: body 0.977 W/kg. Operation of this module in mobile exposure conditions with respect to section 2.1091 of FCC rules is limited as follows: The antenna (s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. End-users and installers must be provided with antenna installation and transmitter operating conditions for satisfying RF exposure compliance. The antenna(s) used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

CE: This device has shown compliance with the conducted emissions limits in 15.107, 15.207, or 18.307 adopted under FCC 02-157 (ET Docket 98-80). The device may be marketed after July 11, 2005, and is not affected by the 15.37(j) or 18.123 transition provisions.