

HOLIDAY SPECIAL

December 2007

TT™ 2400H

High Output Power 1 Watt Bridge with Amplification

Flexible and easy to deploy, this High-Power bridge delivers outstanding performance in a simple, cost-effective package. It is designed for outdoor all-weather deployment and offers a robust weatherproof case that can protect itself against rain, wind, and snow.

Features Include:

- Web & SNMP Based Management, EZManager
- VLAN Transparent Support
- Adjustable Transmit TX Power
- 64/128 bit WEP, MAC Address Filter Intra-BSS Traffic Blocking (Layer 2 Isolation)
- WDS (Wireless Distribution System) Available in AP Mode
- Configurable ACK Time Out for Long Distance



Technical Specifications:

Standard Compliance: 802.11b

Modulation: (DSSS) Direct Sequence Spread Spectrum

Frequency Band: 2.4GHz: IEEE 802.11b ISM Band

USA FCC: 2.412 GHz ~ 2.462 GHz Ch1- Ch11

Output Power: 1 Watt (30dBm)

Mounting: For both wall and pole mount

Enclosure: Die Cast Aluminum NEMA 4 Box

Antenna Connector: N Type Female

Operating Temperature: -40° C to + 70° C

Dimension & Weight: 7.5" x 9" x 2.75", 7 lbs

\$295

While Supplies Last...

Min Qty: 10 Pcs

#11-169 AP

#11-170 SU

**Take advantage of this special offer and call
301-309-8500 and press #1 for Sales**

*Teletronics International features great deals on select Teletronics Products! Don't wait!
Call 301.309.8500 for more information.*

All Rights Reserved. Copyright 2007 Teletronics International, Inc. 2 Choke Cherry Road, Rockville, MD 20850

www.teletronics.com Email: sales@teletronics.com